

HM 46 A AKKU

TECHNISCHE DATEN/TECHNICAL SPECIFICATIONS

BESTELL-NR./ORDER NUMBER: 86-0460-15-03



46 cm	4 – 7 cm	0 - 500 m ²	ABHÄNGIG VOM AKKU / DEPENDING ON THE BATTERY	1-GANG 1-SPEED	B&S POWERHEAD 1350 W @ 2800 U/MIN / RPM	< 90 dB(A)	30 kg 89 X 53 X 44 cm

STARTER:

STARTKOPF AM HOLM/ START BUTTON AT THE HANDLEBAR

PASSENDEN ZUBEHÖR / MATCHING ACCESSORIES

ANTI-BRUCH-SYSTEM NACHRÜSTSATZ

/ ANTI-BREAKAGE-SYSTEM RETROFIT KIT:



HOLMVERLÄNGERUNG / HANDLEBAR EXTENSION:



DREIRADADAPTER / TRICYCLE ADAPTER:



AKKUS ZUR AUSWAHL / BATTERIES TO CHOOSE:

MAX. SPANNUNG / MAX. VOLTAGE:

NENNSPANNUNG / NOMINAL VOLTAGE:

KAPAZITÄT / CAPACITY:

LADEZEIT / CHARGING TIME:

LAUFZEIT / RUN TIME:

BESTELL-NR. / ORDER-NR.:

2 AH	4 AH	5 AH
82 V	82 V	82 V
72 V	72 V	72 V
144 WH	288 WH	360 WH
30 MIN	< 40 MIN	< 60 MIN
< 20 MIN	< 40 MIN	< 60 MIN
992-2-0602	992-2-0603	992-2-0590